

# VGB-600D

## Chewing Gum Coating System



### Features:

With CIP online cleaning system, the D-type machine in addition to possess all the functions and characteristics of the C-type machine, but also have the following characteristics:

- Different parts of the main machine are collocated with a number of nozzles for cleaning machine on-line.
- Configured the independent cleaning liquid booster distribution station to make sure the pressure of cleaning liquid from every spray head get up to 0.6Mpa and wash the coating machine effectively.
- Configured the cycle cleaning and drainage systems for the cleaning process to choose
- Under the control of the PLC, can program a number of cleaning procedures.
- Under the control of the PLC, dry the remanent water of each nozzle by compressed air.
- Under the control of the PLC, implement fully automatic washing and drying process.



Technical parameter	VGB-600D
Production capacity	600kg/run, material density :1g/cm <sup>3</sup>
Speed-adjusting range of coating drum	2-10rpm
Diameter of hole	3mm
Motor power of main machine	5.5Kw
Regulating range of hot air temperature	Normal temperature 80℃
Filtration accuracy of hot air	0.5um
Motor power of hot air machine	5.5Kw
Motor power of exhaust air machine	15.0Kw
Motor power of peristaltic pump	0.18Kw
Noise	≤75db

# VGB-600D

## Chewing Gum Coating System

