

TFM-280

DESICCANT FILLING AND SEALING MACHINE



Desiccant Filling and Sealing Machine



The latest design with safety cover, better performance and security guaranteed.

Combination and Performance:

- Desiccant Filling&Sealing Machine is used to achieve the cover of the automatic management cover, automatic feeding, automatic washer assembly, product testing, product count, finished out of the material, removing waste and other functions.
- With clear function
- With counting function
- With sealing temperature setting adjustment function, temperature range from 60-200℃.
- The device itself should be enough security features, device overload protection, emergency stop buttons. Machinery equipment and accessories shall comply with national safety standards for environmental safety, mechanical safety, electrical safety, and so on all aspects.
- Peripherals vibration plate, linear vibrators, strap lines and PLC board adopts the European standard connections.
- All sensor wiring using quick-change connector for easy maintenance and replacement
- Cap the components in the assembly process and assembly is completed should not be any lower quality of damage, that no form of semi-finished and finished products in the production process of wear, scratches, crushing, staining, foreign substances, oil pollution, product deformation and other quality problems.

Technical Data	TFM-280
Output	35-40 caps/min
Power supply	3.5Kw 220v/50Hz,1Phase
Compressive air	5-8 Bar
Overall size	2500×2500*1800mm
Weight	600kg

SaintyCo also offer:

Encapsulation Solutions

Tablet Compression Solutions

Coating Systems

Cartoning Systems

Blister Packing Solutions

